

TIXOWAY ANTIMANCHAS ACQUA



FAMILY PAREDES Y TECHOS / SISTEMAS TINTOMÉTRICOS

LINE ANTIMANCHAS

DESCRIPTION AND NATURE

Matt water-based paint with excellent coverage, ideal for sealing and covering dry marks from damp, smoke, grease or coffee stains, crayon or pen marks, etc. Total coverage in two coats: the first seals and the second covers stains completely.

USAGES

Indoors
Cement
Plaster
Concrete
Spotted smoke, nicotine, oil

PROPERTIES

Anti-spots
Makes a film
Fast drying
Low odour
Quick and easy to apply.
Covers stains with two coats
Easy to paint over
Non Yellowing
Excellent covering
Very effective on non-water soluble stains
With anti-mould additive

TECHNICAL CHARACTERISTICS

Referencia Color	TIXOWAY ANTIMANCHAS ACQUA
Finish	Matt
Specific weight	1,45± 0,05 kg/l
Viscosity	100 +/- 15 PO
Solids in volume	44± 1
Solids in weight	63± 1
VOC	Cat. i/BA 140/140 (2007/2010):0,62 g/l
Aproximated performance by coat	6-8 m ² /L
Dry to touch	(20°C HR: 60%): 30min
Dry to repaint	(20°C HR: 60%): Once dry
Washability	CLASE 1

SURFACE PREPAIRING

New surfaces

- Cement and plaster mortar:
- Wait until completely set (minimum 30 days).
- Wait until completely dry (max. 15-20% humidity).
- The base must be free from foreign products and/or residue.
- Clean off any efflorescence and neutralise alkaline surfaces.
- Apply to dust-free, dry surfaces.
- Use appropriate plaster to fill any defects in the base (to make a suitable selection, see the PREPARING BASES family for

TIXOWAY ANTIMANCHAS ACQUA

lines corresponding to powder plaster and prepared fillers).

- For grease stains see restoration/maintenance.

Restoring and maintenance

- Remove badly adhered old paint.
- Apply directly to surfaces stained with smoke, nicotine, greases or oils.
- In extreme cases it is advised that you clean the surface previously with hot water and detergents.
- Leave it to fully dry and then paint.

WAY OF USE

Application notes

- Shake the product until it is evenly mixed.
- Dilute depending on the application and even out completely.
- Although it is a monolayer product, in difficult cases it is recommended that you use three coats, respecting drying times between each coat.
- On new surfaces, use as you would any plastic paint.
- If painting over satin or gloss paint sand down beforehand to ensure better adhesion.
- Repaintable with plastic paints from the Montó (Family 1) range.
- Colourable with water-based dyes (max. 3%).
- Paint with preservative to prevent microbial damage. With anti-mildew preservative (Contains: zinc pyrithione, octylisothiazolinone and diuron).
- We recommend pre-washing with water and detergent.
- For applications on non-dry 100% moisture stains, it is recommended to use solvent-based stains (Tixoway Antimanchas) because it is more effective in this type of situation.

Solvent for dilution and cleaning

Water

Way of use

Air-less gun

Painting brush

Roller

Aproximate dilution

Fondo: 0-5 %. Acabado: al uso

Fondo: 0-5 %. Acabado: al uso

Fondo: 0-5%. Acabado: Al uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Inner painted old work in good state			
MAX	Emulsión Fijadora/Fijamont	Tixoway Antimanchas Acqua	Tixoway Antimanchas Acqua y/o Pintura Plástica (Familia 1)
STD	Tixoway Antimanchas Acqua	Tixoway Antimanchas Acqua	Tixoway Antimanchas Acqua y/o Pintura Plástica (Familia 1)
Inner painted old work in good state			
MAX	Emulsión Fijadora/Fijamont	Tixoway Antimanchas Acqua	Tixoway Antimanchas Acqua y/o Pintura Plástica (Familia 1)
STD	Tixoway Antimanchas Acqua	Tixoway Antimanchas Acqua	Tixoway Antimanchas Acqua y/o Pintura Plástica (Familia 1)
Paints with stains			
MAX	Tixoway Antimanchas Acqua	Tixoway Antimanchas Acqua	Tixoway Antimanchas Acqua y/o Pintura Plástica (Familia 1)
STD	Tixoway Antimanchas Acqua	Tixoway Antimanchas Acqua	Tixoway Antimanchas Acqua y/o Pintura Plástica (Familia 1)

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.75 L, 4 L, 12 L



**FAMILY
LINE**

DESCRIPTION AND NATURE

Matt water-based paint with excellent coverage, ideal for sealing and covering dry marks from damp, smoke, grease or coffee stains, crayon or pen marks, etc. Total coverage in two coats: the first seals and the second covers stains completely.

USAGES

PROPERTIES

- Anti-spots
- Makes a film
- Fast drying
- Low odour
- Quick and easy to apply.
- Covers stains with two coats
- Easy to paint over
- Non Yellowing
- Excellent covering
- Very effective on non-water soluble stains
- With anti-mould additive

TECHNICAL CHARACTERISTICS

Referencia Color	
Finish	Matt
Specific weight	1,45± 0,05 kg/l
Viscosity	100 +/- 15 PO
Solids in volume	44± 1

Fecha de Alta

05-01-2016

Versión

8 - 17/11/2025

Solids in weight	63± 1
VOC	Cat. i/BA 140/140 (2007/2010):0,62 g/l
Aproximated performance by coat	6-8 m ² /L

Dry to touch	(20°C HR:60%): 30min
Dry to repaint	(20°C HR:60%): Once dry
Washability	CLASE 1

SURFACE PREPAIRING

New surfaces

- Cement and plaster mortar:
- Wait until completely set (minimum 30 days).
- Wait until completely dry (max. 15-20% humidity).
- The base must be free from foreign products and/or residue.
- Clean off any efflorescence and neutralise alkaline surfaces.
- Apply to dust-free, dry surfaces.
- Use appropriate plaster to fill any defects in the base (to make a suitable selection, see the PREPARING BASES family for lines corresponding to powder plaster and prepared fillers).
- For grease stains see restoration/maintenance.

Restoring and maintenance

- Remove badly adhered old paint.
- Apply directly to surfaces stained with smoke, nicotine, greases or oils.
- In extreme cases it is advised that you clean the surface previously with hot water and detergents.
- Leave it to fully dry and then paint.

WAY OF USE

Application notes

- Shake the product until it is evenly mixed.
- Dilute depending on the application and even out completely.
- Although it is a monolayer product, in difficult cases it is recommended that you use three coats, respecting drying times between each coat.
- On new surfaces, use as you would any plastic paint.
- If painting over satin or gloss paint sand down beforehand to ensure better adhesion.
- Repaintable with plastic paints from the Montó (Family 1) range.
- Colourable with water-based dyes (max. 3%).
- Paint with preservative to prevent microbial damage. With anti-mildew preservative (Contains: zinc pyrithione, octylisothiazolinone and diuron).
- We recommend pre-washing with water and detergent.
- For applications on non-dry 100% moisture stains, it is recommended to use solvent-based stains (Tixoway Antimanchas) because it is more effective in this type of situation.

Solvent for dilution and cleaning

Water


Way of use	Approximate dilution
Air-less gun	Fondo: 0-5 %. Acabado: al uso
Painting brush	Fondo: 0-5 %. Acabado: al uso
Roller	Fondo: 0-5%. Acabado: Al uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Inner painted old work in good state			
MAX	Emulsión Fijadora/Fijamont	Tixoway Antimanchas Acqua	Tixoway Antimanchas Acqua y/o Pintura Plástica (Familia 1)

TIXOWAY ANTIMANCHAS ACQUA



STD	Tixoway Antimanchas Acqua	Tixoway Antimanchas Acqua	Tixoway Antimanchas Acqua y/o Pintura Plástica (Familia 1)
------------	---------------------------	---------------------------	--

Inner painted old work in good state

MAX	Emulsión Fijadora/Fijamont	Tixoway Antimanchas Acqua	Tixoway Antimanchas Acqua y/o Pintura Plástica (Familia 1)
STD	Tixoway Antimanchas Acqua	Tixoway Antimanchas Acqua	Tixoway Antimanchas Acqua y/o Pintura Plástica (Familia 1)

Paints with stains

MAX	Tixoway Antimanchas Acqua	Tixoway Antimanchas Acqua	Tixoway Antimanchas Acqua y/o Pintura Plástica (Familia 1)
STD	Tixoway Antimanchas Acqua	Tixoway Antimanchas Acqua	Tixoway Antimanchas Acqua y/o Pintura Plástica (Familia 1)

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

PACKINGS

0.75 L, 4 L, 12 L