

Fecha de Alta

20-12-2013

Versión

2 - 21/04/2022


FAMILY ANTIHUMEDAD E IMPERMEABILIZAC.

LINE CONSERVACION

DESCRIPTION AND NATURE

Ready-to-use spray product for the preservation and treatment of construction and masonry materials by means of microbial control and control of contamination from moss, algae and fungus.

USAGES

Outdoors/Indoors

Cement

Brick

Concrete

Roofing tiles

Fibre-cement

Infected support

Stone

Floor tile

Product for treating and repairing surfaces prior to painting. Can be repainted using water-based paints

PROPERTIES

- Optimal applicability
- Odourless when dry
- The active materia developes intense and long term reaction
- Do not brings yellowness or discolouring to the final product
- Repaint with water base paints
- Does not change the appearance of the support
- Cleaner with anti-mould preservative
- Deep penetration

TECHNICAL CHARACTERISTICS

Referencia Color	MONTOLIMP SPRAY
Finish	Transparent
Specific weight	0,97± 0,05 kg/l
Solids in volume	3± 1
Solids in weight	3± 1
Aproximated performance by coat	5-6 m ² /L

Dry to touch	1h
Dry to repaint	2h
Colours	Transparent

SURFACE PREPAIRING
New surfaces

No special preparation is required.

For the best results, the surface must be dry.

If you plan to paint the surface following the treatment, follow the technical guidelines for the product to be used.

Restoring and maintenance

Remove any loose or peeling paint.

No special preparation is required.

For the best results, the surface must be dry.

If you plan to paint the surface following the treatment, follow the technical guidelines for the product to be used.

Fecha de Alta

20-12-2013

Versión

2 - 21/04/2022

WAY OF USE

Application notes

Scrub down the affected surfaces using a hard bristle brush, removing any black stains that are visible.

Apply the spray to a dry surface.

Let it sit for 48 hours. Remove the dry moss with a brush or high-pressure water.

Repeat the procedure in the places where the moss was not completely removed.

Do not apply if rain is forecast.

Repaint, preferably with plastic paint

Solvent for dilution and cleaning

Water

Way of use

Spray

Aproximate dilution

Al uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Old paintings in bad state			
MAX		Fijador	Pintura al agua de acabado+ Aditivo Fungicida
STD	Montolimp Spray	Pintura al agua de acabado	Pintura al agua de acabado
Old painting in good state			
MAX	Montolimp Spray	Pintura al agua de acabado+ Aditivo Fungicida	Pintura al agua de acabado+ Aditivo Fungicida
STD	Montolimp Spray	Pintura al agua de acabado+ Aditivo Fungicida	Pintura al agua de acabado+ Aditivo Fungicida
New work			
MAX		Fijador	Pintura al agua de acabado+ Aditivo Fungicida
STD	Montolimp Spray	Pintura al agua de acabado	Pintura al agua de acabado
Infected support			
MAX			
STD	Montolimp Spray	Pintura al agua de acabado+ Aditivo fungicida	Pintura al agua de acabado+ Aditivo fungicida

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances.As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

503201

MONTOLIMP SPRAY



Fecha de Alta

20-12-2013

Versión

2 - 21/04/2022

PACKINGS

0.5 L