



Road Marking Acrylic Paint

Acrylic Solvent Based Paint



Covering Power: 1 - 1,4 m²/lt



Drying: 15 - 17 seconds



Dilution: Application with road marking machine: Ready for use.

Roller or brush: 5% VECHRO thinner No 1.

Spray: 10-15% Vechro Thinner No 1.



Packing: 1kg, 5kg, 23kg, 25kg

Application: Brush, Roller, Spraygun, Special Road-marking Machine

GENERAL CHARACTERISTICS

Solvent paint based on acrylic resins, suitable for road marking. It has great adhesion and abrasion and wear resistance. Its brightness keeps vigorous even after late use in all weather conditions. Dries so fast, that the surface is ready for use 60' after application depending on weather conditions.

Paint's mixture with special glassy spherules (glass beads), make this product reflex.

In addition to that its mixture with special sand increases nonskid results.

TECHNICAL CHARACTERISTICS

Texture	Mat sheen up to 4-10 units 60°.
Specific weight	1,48- 1,52 kg/lt (white).
Covering power	1-1,4 m ² /lt
Dilution	Application with road marking machine: Ready for use. Roller or brush: 5% Vechro thinner No 1. Spray: 10-15% Vechro Thinner No 1.
Drying	Dry to touch in 15' -17'. Dry to use in 1 hour depending on weather conditions.
Mixture with glassy spherules	300 gr of glassy spherules in 800 - 1000 gr of paint for 1m ²
VOC class	Not applicable.
Shades	White, yellow, black and other shades upon request.



SURFACE PREPARATION

The surface should be well cleaned from dust and old cropped paints before application.

APPLICATION

Stir well paint before use as well as during working. Use the road marking paint at the proper net film thickness.

CLEANING EQUIPMENT

Strain well your tools from paint back to the pot and clean immediately with Vechro No 1 thinner.

APPLICATION CONDITIONS

Temperature 8-30°C and relative humidity lower than 65%. Contrary weather conditions may degrade product's quality and drying properties.

STORAGE

Store in a cool place, protect from freezing and sun exposure. Close the can well after application to keep in good condition. Recover unused paint for re-use. Reuse of paint can effectively minimize the product's life cycle environmental impact.

LABELLING

FOR PROFESSIONAL USE ONLY / Available SDS for professionals.

* More information in Safety Data Sheets (SDS).

SAFETY

Read the tag on the back side of the product.



The technical data and instructions included in this technical leaflet are based on audits of confidential laboratories and result of the knowledge and experience of the company's scientific staff. The quality of the product is guaranteed by the company, which is aligned with the requirements of ISO 9001, 14001 and EMAS. As a producer, we are not responsible for any damage or damage caused if the product has not been used for proper application and in accordance with its instructions for use.